

In The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-14. Cancelled.

15. (Currently Amended) A system for distributing first and second materials comprising:

first and second sources holding the first and second materials, respectively;
a plurality of distribution units; and

a nurse distribution mechanism configured to selectively communicate each of
~~coupled between~~ the sources with and each of the distribution units by which each of
the first and second materials from the respective first and second sources can be
individually transmitted to the plurality of distribution units,

wherein the plurality of distribution units includes a plurality of meters,

wherein each of the meters includes a receiver having first and second inlets,

wherein the nurse distribution mechanism includes first and second pluralities of
distribution lines,

wherein each off the first plurality of distribution lines is coupled between the
first source and the first inlet of the receiver of a respective one of he plurality of
meters, and

wherein each of the second plurality of distribution lines is coupled between the second source and the second inlet of the receiver of a respective one of the plurality of meters.

16. (Original) The system of claim 15,

wherein whether the respective receivers receive the first material or the second material by way of the respective first or second inlets is determined by one of a setting on a respective nurse inductor box and a status of air being supplied to at least one of the first and second sources.

17-26. Cancelled.

27. (New) A system for distributing first and second materials comprising:

first and second sources holding the first and second materials, respectively;
a plurality of distribution units; and

a nurse distribution mechanism configured to selectively communicate each of the sources with each of the distribution units by which each of the first and second materials from the respective first and second sources can be individually transmitted to the plurality of distribution units,

wherein the plurality of distribution units includes a first plurality of meters and a second plurality of distribution units includes a second plurality of meters, wherein a respective one of each of the first and second pluralities of meters is included within each of the respective distribution units.

28. (New) The system of claim 27, wherein the first material from the first source is transmitted to the plurality of distribution units at a first time, and the second material

from the second source is transmitted to the plurality of distribution units at a second time.

29. (New) The system of claim 27, wherein the nurse distribution mechanism includes first and second pluralities of distribution lines, wherein each of the first plurality of distribution lines is coupled between the first source and a respective one of the first plurality of meters, and wherein each of the second plurality of distribution lines is coupled between the second source and a respective one of the second plurality of meters.

30. (New) The system of claim 27, wherein each of the first and second pluralities of meters is capable of being turned on and turned off by way of at least one signal provide by at least one of an electrical signal transmitted by wire, a wireless signal, and a GPS signal.

31. (New) The system of claim 27, wherein the nurse distribution mechanism comprises:

- a first primary line coupled to the first source;

- a second primary line coupled to the second source;

- a first nurse header coupled to each of the first and second primary lines; and

- a first plurality of secondary lines, each of which is coupled to the first nurse header and additionally is coupled to a respective one of the plurality of distribution units, wherein at least some of the plurality of distribution units are coupled to the first nurse header by the plurality of secondary lines.

32. (New) The system of claim 31, wherein the nurse distribution mechanism further comprises:

- a third primary line coupled to the first source;
- a fourth primary line coupled to the second source;
- a second nurse header coupled to each of the third and fourth primary lines; and
- a second plurality of secondary lines, each of which is coupled to the second nurse header and additionally is coupled to a respective one of the plurality of distribution units, wherein a first subset of the plurality of distribution units are coupled to the first nurse header by the first plurality of secondary lines, and another subset of the plurality of distribution units are coupled to the second nurse header by the second plurality of secondary lines.

33. (New) The system of claim 32, further comprising a third source holding a third material and a third primary line coupled to the third source, wherein the first nurse header is coupled to each of the first, second and third primary lines.

34. (New) The system of claim 31, wherein all of the plurality of distribution units are coupled to the first nurse header by the first plurality of secondary lines.

35. (New) The system of claim 31, wherein whether the first plurality of secondary lines transmit the first material or the second material is determined by at least one nurse inductor box.

36. (New) The system of claim 27, wherein the nurse distribution mechanism further comprises:

first and second primary lines coupled to the first and second sources,
respectively;

a plurality of secondary lines coupled to at least some of the distribution units,
wherein each of the plurality of secondary lines is coupled to a respective one of the
distribution units; and

a coupling mechanism that, in a first position, couples the first primary line to
the plurality of secondary lines and, in a second position, couples the second primary
line to the plurality of secondary lines.

37. (New) The system of claim 36, wherein the coupling mechanism is manually
actuatable.

38. (New) The system of claim 27,

wherein each of the distribution units includes at least one meter that one of
delivers materials volumetrically and delivers materials singularly, wherein the first and
second materials are one of different from one another and the same as one another, and
wherein each of the first and second materials is selected from the group consisting of
seed, fertilizer, and pesticide.

39. (New) A system for distributing first and second materials comprising:

first and second sources holding the first and second materials, respectively;
a plurality of distribution units; and

a nurse distribution mechanism configured to selectively communicate each of
the sources with each of the distribution units by which each of the first and second

materials from the respective first and second sources can be individually transmitted to the plurality of distribution units,

wherein the plurality of distribution units includes a plurality of meters, and wherein each of the meters includes first and second receiver compartments.

40. (New) The system of claim 39, wherein communication between the compartments of the respective meters and metering devices of those respective meters is controlled by way of a flapper.

41. (New) The system of claim 40, wherein the nurse distribution mechanism includes first and second pluralities of distribution lines, wherein each of the first plurality of distribution lines is coupled between the first source and the first receiver compartment of a respective one of the plurality of meters, wherein each of the second plurality of distribution lines is coupled between the second source and the second receiver compartment of a respective one of the plurality of meters, and wherein the respective flapper of each respective meter determines whether the meter distributes material from its respective first receiver compartment or from its respective second receiver compartment.

42. (New) The system of claim 41, wherein the flapper of each of the meters is controlled from a remote location.

43. (New) A system for distributing first and second materials comprising:

first and second sources holding the first and second materials, respectively;
a plurality of distribution units; and

a nurse distribution mechanism configured to selectively communicate each of the sources with each of the distribution units by which each of the first and second materials from the respective first and second sources can be individually transmitted to the plurality of distribution units, wherein the nurse distribution mechanism comprises:

first and second primary lines coupled to the first and second sources, respectively;

a plurality of secondary lines coupled to at least some of the distribution units, wherein each of the secondary lines is coupled to a respective one of the distribution units; and

a valve coupled to the first and second primary lines and to each of the plurality of secondary lines.

44. (New) The system of claim 43, wherein the valve is positioned closer to the first and second sources than to the distribution units.

45. (New) The system of claim 43, wherein the valve is capable of combining the first and second materials to form a combination material, and capable of providing the combination material by way of the plurality of secondary lines to the distribution units.